





This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
4		AS DRAWN BY CANAM.	9/14/2012	JAG	
5		CH'D MATERIAL FROM 4340, ADDED NOTE, CORRECTED TOP VIEW PROJECTION.	11/7/2012	RJC	SE
6	14-0126	CH'D TITLE BLOCK WAS RED BARN IS DART, ADDED MACHINE ENGRAVE NOTE, CH'D DIMS WAS .030 X 45° IS 4X .03 X 45°, WAS .060 X 45° IS 2X .06 X 45°, WAS .030 X 45° IS 2X .03 X 45°, CH'D TOLERANCE ON NON-CRITICAL DIMENSIONS.	8/13/2014	DPD	RW



SECTION A-A



NOTES:

1. NICKEL PLATE .0004 - .0006, BAKE AFTER PLATING.
2. CALIBRATE HOLE AFTER HEAT TREATING AND POLISH ROLLER AREA.
3. MACHINE ENGRAVE BATCH NUMBER.

DART
AEROSPACE

TITLE		REV
DWG NO.		6
MATL	4140/4142	DRAWN BY: CANAM
UNLESS OTHERWISE SPECIFIED		APPROVED <i>D. Weil</i>
DIMENSIONS ARE IN INCHES		HEAT TREAT 44-46 HRC
.XXX ± .005	FRACTIONS ± 1/8	FINISH SEE NOTE 1
.XX ± .01	ANGLES ± .5°	SPEC
.X ± .1		USED ON MODEL
1. BREAK ALL SHARP EDGES .015 X 45° OR .015R		
2. DIMENSIONAL LIMITS APPLY AFTER PLATING		
SCALE	1:1	DATE 3/6/2000
		SHEET 1 OF 1

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS
			C45-12-3	1	LOCK	4140/4142	1-1/4 X 2 X 5-1/8